



# Becatech

Interconnective Power



**Jam nut  
(Contramoor)**

## Technical Specification :

Material: nickel plated brass.

Rated temperature: -60°C to 200°C.

The contact is achieved when tightening the jam nut by the cutting edges scratching the coated layer of the housing.

*Suitable for all metric cable glands used in grounding and EMC applications.*

## Application :

For use on the inside of painted, anodized or powder coated enclosures.

Can be used with metric SKINTOP and SKINDICHT cable glands for applications where electromagnetic compatibility (EMC) is required.

Resistant to high chemical and mechanical loads.

Article	Thickness mm	Wrench Size mm	Overall Diameter mm
M12 x 1.5	4.7	15.0	17.3
M16 x 1.5	4.7	19.0	21.9
M20 x 1.5	4.7	24.0	27.7
M25 x 1.5	5.2	30.0	34.6
M32 x 1.5	5.7	36.0	41.5
M40 x 1.5	6.5	46.0	53.1
M50 x 1.5	6.5	60.0	69.3
M63 x 1.5	7.0	70.0	80.8
M75 x 1.5	8.0	85.0	95.0
M72 x 2	10.0	85.0	98.0
M90 x 2	10.0	102.0	114.0
M110 x 2	12.0	124.0	135.0

Becatech B.V.  
Middenweg 18  
3930 Hamont-Achel

info@becatech.be  
www.becatech.be  
+32 (0)11 19 29 45

IBAN BE89363217265185  
VAT BE0777.903.079  
CoC 0777.903.079