



Becatech

Interconnective Power



**PVC sheathing pipe wire
(H05VV-F)**

Cable Structure :

Conductor: flexible bare copper (class 5).

Insulation: PVC YI2.

Outer sheath: PVC YM2.

Technical Specification :

Rated temperature: -5°C to 50°C.

Rated conductor temperature: 60°C.

Rated bending radius fixed: 3 x ϕ .

Rated bending radius moving: 5 x ϕ .

Flame retardant according to IEC 60332-1-2.

Application :

Suitable for medium mechanical in household, kitchen and office rooms. For household appliances even in damp rooms.

Suitable for cooking and heating devices if provided that the cable is not in contact with hot parts or is exposed to heat radiation.


NOT for permanent outdoor use.

Core x mm ²	Overall Diameter mm	Cu Weight	Weight / 1000 (kg)	Available Colors
2x0.75	5.8	14.4	52	WE
2x1	6.5	19.0	65	BK/WE
2x1.5	7.5	29.0	90	BK/WE
2x2.5	9.0	48.0	115	BK/WE
3g0.75	6.5	21.6	70	BK/WE
3g1	7.0	29.0	80	BK/WE
3g1.5	8.2	43.0	115	BK/WE/GY

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

3g2.5	9.8	72.0	175	BK/WE
4g0.75	6.7	29.0	75	BK/WE
4g1	7.2	38.4	92	BK/WE
4g1.5	9.2	58.0	145	BK/WE
4g2.5	10.7	96.0	210	BK/WE
5g0.75	7.5	36.0	96	BK/WE
5g1	8.0	48.0	113	BK/WE
5g1.5	10.2	72.0	175	BK/WE
5g2.5	13.0	120.0	260	BK/WE

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079