



Becatech

Interconnective Power



Harmonized PVC wire (H07V2-K)

Cable Structure :

Conductor: flexible bare copper according to IEC 60228 (class 5).
Insulation: color based on PVC, TI3 quality.

Technical Specification :

Rated temperature: -10°C to 90°C.
Minimum installation temperature: 5°C.
Rated bending radius: 4 x ϕ .
Flame resistant according to IEC 60332-1-2.

Application :


Can be used in low voltage switchgear and distribution equipment, internal cabling of equipment. Can be used in protected installation in pipe and cabling shafts, as in installation and assembly. Wiring in professional lighting equipment.

Core x mm ²	Overall Diameter mm	Weight (kg/km)
1x0.5	2.5	10
1x0.75	2.7	13
1x1	2.8	15
1x1.5	3.0	20
1x2.5	3.5	30
1x4	4.0	45
1x6	4.6	65
1x10	6.4	115
1x16	8.1	180

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

1x25	9.5	265
1x35	10.6	355
1x50	13.1	505
1x70	14.8	685
1x95	16.6	890
1x120	17.8	1115
1x150	20.2	1400
1x185	21.9	1675
1x240	24.3	2180
1x300	27.7	2790
1x400	31.6	3650

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079