



Becatech

Interconnective Power



**Harmonized PVC accu-welding
power cable
(hi-flex)**

Cable Structure :

Conductor: flexible bare copper.
Outer sheath: PVC.
Available colors: black, red.

Technical Specification :

Rated temperature while using: 5°C to 70°C.
Rated conductor temperature: 70°C.

Application :


For connection of low voltage power supplies for accumulators, among other things. (used in ship installations as a power supply for, for example bow thrusters).

Core x mm ²	Overall Diameter mm	Weight Cable (kg/km)	Color
1x10	7.3	130	BK
1x10	7.3	130	RD
1x16	8.7	200	BK
1x16	8.7	200	RD
1x25	10.5	300	BK
1x25	10.5	300	RD
1x35	12.0	410	BK
1x35	12.0	410	RD
1x50	13.8	565	BK
1x50	13.8	565	RD
1x70	15.9	780	BK

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

1x70	15.9	780	RD
1x95	18.2	1050	BK
1x95	18.2	1050	RD
1x120	20.1	1300	BK
1x120	20.1	1300	RD

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079