



Becatech

Interconnective Power



Audio and data defense cable (PVC/TCWB/PVC)

Cable Structure :

Conductor: flexible tinned annealed copper.

Insulation: PVC.

Screen: tinned copper wire braid.

Outer sheath: PVC.

Technical Specification :

Nominal voltage: 440V.

Rated temperature: 0°C to 70°C.

Rated bending radius: 6 x Ø.

Core x mm ²	Diameter Over laid Up cores mm	Diameter Of braid Wire mm	Diameter Over Coll. Screen mm	Overall Diameter mm	Weight (kg/km)
2x0.22	2.4	0.10	2.9	3.9	23
3x0.22	2.6	0.10	3.1	4.1	27
4x0.22	2.9	0.10	3.4	4.4	32
6x0.22	3.6	0.15	4.4	5.6	55
8x0.22	4.0	0.15	4.8	5.9	69
12x0.22	5.0	0.15	5.8	6.9	83
15x0.22	5.5	0.15	6.3	7.6	97
18x0.22	6.0	0.15	6.8	8.2	110
20x0.22	6.4	0.15	7.2	8.5	120
25x0.22	7.2	0.15	8.0	9.5	150
36x0.22	8.4	0.15	9.2	10.8	200
50x0.22	10.0	0.20	11.0	12.6	270
60x0.22	10.8	0.20	11.8	13.4	310

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079