

Becatech

Interconnective Power



**Plug-in sleeve
(verbindingsmof)**

Technical Specification :

Halogen free according to DIN EN 50642 (VDE 0604-2-100).

Resistant to:

- Exhaust gases containing hydrochloric acid.
- Exhaust gases containing sulfuric acid.
- Liquid ammonia.
- Gaseous ammonia.
- Petrol.
- Diesel fuel.
- Aqueous fertilizer salt.
- Photo developer.
- Vinegar (wine vinegar).
- Antifreeze.
- Fruit juices.
- Uric acid aqueous.
- Fuel oil.
- Sea water.
- Methanol.
- Milk.
- Mineral oil.
- Vegetable and animal oils.
- Petroleum.
- Propane gaseous.
- Hydrochloric acid.
- Sulfuric acid.
- Detergent.


Application :

Used for the sand-tight connection of kabuflex pipes.
Suitable for in the ground.

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

Type	Inner Diameter mm	Overall Diameter mm	Contents	Weight PU/kg	Total Length mm
40	40	47.1	1	0.016	83.0
50	50	57.9	1	0.024	100.0
63	63	73.0	1	0.036	110.0
75	75	84.2	1	0.060	130.0
90	90	100.5	1	0.135	148.0
110	110	122.8	1	0.180	162.0
120	120	130.9	1	0.185	196.0
125	125	142.2	1	0.200	200.0
145	145	157.2	1	0.274	219.0
160	160	173.9	1	0.395	221.0
175	175	193.0	1	0.299	222.0
200	200	211.7	1	0.430	190.0

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079