

Becatech

Interconnective Power



Thin-walled flexible shrink tubing (heat shrink tubing)


Technical Specification :

Shrinking tube type: H-2F(Y/G).
Flame retardant according to VW-1.
Self-extinguishing.
Rated temperature: -55°C to 135°C.
Minimum shrink temperature: 70°C.
Minimum full shrink temperature: 0°C to 100°C.
Length shrinkage: 0 to 10% maximum.
Quality class material: crosslinked polyolefin.
Available color: green/yellow.

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

Length m	Delivery Inner Diameter mm Minimum	After Shrink Inner Diameter mm Maximum	After Shrink Wall Thickness mm minimum
150	2.4	0.8	0.51
150	3.0	1.0	0.55
75	4.5	1.5	0.60
75	6.0	2.0	0.65
75	9.0	3.0	0.75
50	12.0	4.0	0.75
30	18.0	6.0	0.85
30	24.0	8.0	1.00
30	39.0	13.0	1.15
10	3.0	1.0	0.55
10	4.5	1.5	0.60
10	6.0	2.0	0.65
5	9.0	3.0	0.75
5	12.0	4.0	0.75
5	18.0	6.0	0.85
5	24.0	8.0	1.00

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079