




Becatech

Interconnective Power



**Shielded PVC control cable
(YSLCY-OZ)**

Cable Structure :

Conductor: flexible bare copper (class 5).

Insulation: PVC.

Shielding: tinned copper braid work with a coverage of 75%.

Outer sheath: PVC.

Core identification: black numbered.

Technical Specification :

Rated temperature: -25°C to 70°C.

Rated conductor temperature: 70°C.

Rated bending radius: 10 x ϕ .

Fire behaviour according to 60332-3C, HD405.3, 60811-504, 505 and 506.

Application :

Is used for signal transmissions.


Good resistance to oils and gasoline.

Core x mm ²	Overall Diameter mm	Weight (kg)	Cu Weight (kg/km)
2x0.5	5.3	41	36.0
3x0.5	5.8	49	43.0
4x0.5	6.2	51	49.0
25x0.5	12.4	257	250.0
2x0.75	5.7	49	43.0
3x0.75	6.2	53	52.0
4x0.75	6.7	66	61.0
5x0.75	7.4	79	72.0

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

7x0.75	8.0	102	89.0
12x0.75	10.4	168	138.0
18x0.75	12.0	239	211.0
25x0.75	13.6	328	280.0
2x1	6.1	57	51.0
3x1	6.6	64	62.0
4x1	7.2	78	74.0
5x1	7.8	95	88.0
7x1	8.6	131	112.0
12x1	11.1	205	185.0
18x1	13.1	293	268.0
25x1	15.1	402	354.0
34x1	17.6	552	458.0
2x1.5	6.6	70	65.0
3x1.5	7.2	84	82.0
4x1.5	8.0	106	100.0
5x1.5	8.7	129	119.0
7x1.5	9.6	168	154.0
12x1.5	12.5	283	268.0
18x1.5	14.6	409	373.0
25x1.5	16.6	548	530.0
34x1.5	19.8	758	686.0
50x1.5	23.1	1071	1001.0
2x2.5	8.6	95	92.0
3x2.5	9.1	127	118.0
4x2.5	9.8	161	147.0
2x6	11.3	214	170.0
2x4	9.7	156	120.0

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079